




地址: 浙江省宁波市会展路 181 号 Add: No.181,HuiZhan Road ,Ningbo city, China 315000
电话: (Tel)86-574-87238791, 传真 (Fax) :86-574-87238794 邮编 (P.C) :315000
http://:www.rubbersealing.com E-mail: sales@rubbersealing.com , MSN: towerpacking@hotmail.com

Bubble Cap Tray



[Bubble-Cap trays](#) have numerous applications in refinery and gas plants, due to their effectiveness over a broad range of flow conditions and low susceptibility to fouling. T.C.I provides both standard and custom designs of [Bubble cap trays](#). We can supply not only standard materials such as 410, 304, and 316 Stainless steels, but also provide special materials such as Monel, Alloy 20, and Hastelloy in a variety of cap styles.

标准泡罩参数与尺寸

单位mm

名称	材料类别	I 类 (A3F)			II 类 (1Cr18Ni9Ti)		
		80	100	150	80	100	150
公称直径Dg		80	100	150	80	100	150
泡帽外径 × 壁厚D ₁ × S ₁		80 × 2	100 × 3	158 × 3	80 × 1.5	100 × 1.5	158 × 1.5
泡帽顶部外径D ₃				152			152
升气管外径 × 壁厚D ₂ × S ₂		57 × 3.5	70 × 4	108 × 4	57 × 2.75	70 × 3	108 × 4
总高度H ₁		95	105	107	95	105	107
升气管高度H ₂		57	62	64	57	62	64
泡帽高度H ₃		65	75	73	65	75	73
泡帽顶到齿缝H4 高度	1	40	45		40	45	
	2	35	42		35	42	
	3	30	38		30	38	
支架至泡帽底端高度H5			45			45	
齿缝高度 h	1	20	25	35	20	25	35
	2	25	28		25	28	
	3	30	32		30	32	
齿缝宽度b 1		4	5	R4/13.5	4	5	R4/13.5
齿缝数目n		30	32	28	30	32	28
齿缝间距f		8.35	9.84	17.7	8.38	9.84	17.7