



地址: 浙江省宁波市滨海四路 695 号 Add: No.695,Binghai Rd,Ningbo China 315000
电话: (Tel)86-574-87238791, 92, 93 传真 (Fax) :86-574-87238794 邮编 (P.C) :315000
<http://www.column-packing.com> www.rubbersealing.com Email: sales@column-packing.com



F1 FLOAT VALVE

Specifications

The float valve tray is installed on adjusted or on existing column attachment.
Material:SS304, SS316L, Ti, Carbon steel, PP, etc Steel, Carbon steel, Plastics
Types::Bubble cap trays/Blister trays, Floating valve trays, Vertical trays, Sieve tray, etc.
The float valve are installed on the height connecting with pipes. When the liquid rises, the floating ball rise and shut off through the lever arm, when the water goes down, the pipes are open, the medium will flow in and reach their height.
The float valve are mainly used in industrial water treatment, chemical processing industry..



宁波天大化工设备科技有限公司

TIANDIA CHEMICAL INDUSTRIAL(TCI) CO., LTD

地址: 浙江省宁波市滨海四路 695 号 Add: No.695,Binghai Rd,Ningbo China 315000
 电话: (Tel)86-574-87238791, 92, 93 传真 (Fax) :86-574-87238794 邮编 (P.C) :315000
<http://www.column-packing.com> www.rubbersealing.com Email: sales@column-packing.com

No.	TYPE	Basic data		TRAY PLATE THICK S	DIMENSIONS					Material
		Thickness δ	weight kg		H	L	a	b	c	
1	F1Q-4A	1.5	0.0246	4	12.5	16.5	9.7		34.8	0Cr13
2	F1Z-4A	2	0.0327				10.2	5.3	34.6	
3	F1Q-4B	1.5	0.0251				9.7	5.4	34.8	0Cr18Ni9
4	F1Z-4B	2	0.0333				10.2	5.3	34.6	
5	F1Q-4C	1.5	0.0253				9.7	5.4	34.8	0Cr17Ni12Mo2
6	F1Z-4C	2	0.0335				10.2	5.3	34.6	
7	F1Q-3A	1.5	0.0243	3	11.5	15.5	9.7	5.4	33.8	0Cr13
8	F1Z-3A	2	0.0324				10.2	5.3	33.6	
9	F1Q-3B	1.5	0.0248				9.7	5.4	33.8	0Cr18Ni9
10	F1Z-3B	2	0.0330				10.2	5.3	33.6	
11	F1Q-3C	1.5	0.0250				9.7	5.4	33.8	0Cr17Ni12Mo2
12	F1Z-3C	2	0.0332				10.2	5.3	33.6	
13	F1Q-2B	1.5	0.0246	2	10.5	14.5	9.7	5.4	32.8	0Cr18Ni9
14	F1Z-2B	2	0.0327				10.2	5.3	32.6	
15	F1Q-2C	1.5	0.0247				9.7	5.4	32.8	0Cr17Ni12Mo2
16	F1Z-2C	2	0.0329				10.2	5.3	32.6	